

ANTAROX BL-225



Propoxyated ethoxylated linear alcohol
Concentration > 99 %

Physical and chemical properties

Polarity: Nonionic
Density: 1.02 g/cm³
Boiling point: 200 °C
Viscosity (25°C): 142 mps
Flash point (Cleveland open cup): 190 °C

Specification

Appearance at 25°C: clear to slightly hazy liquid
Colour (Gardner): 3 max.
Water (K. Fischer): 0.5 %
Cloud point at 1 %: 25 –29 °C
Neutralisation number to pH = 7 (mg KOH/g): max. 0.5

Packaging

Plastic bottle.
5 or 10 kg net weight.

Classification

CAS No.: 68603-25-8
HS-No.: 34021300
Non-hazardous according to current regulations.
EEC-Labeling
Symbol: Xi, N
R: 41, 51/53
S: 25, 36/37/39, 61

Safety recommendations and additional information can be found in the Material Safety Data Sheet (MSDS).

Application

■ **Low foaming surfactant for brazing flux suspensions**
(up to 50 °C)

Recommended concentration:
0.1 to 0.2%

MANAGEMENTSYSTEM



DQS – certified according

DIN EN ISO 9001:2000
Reg.-No. 360447 QM

ISO/TS 16949:2002
Reg.-No. 360447 TS2

NOCOLOK is registered trademark of
Solvay Fluor GmbH, Germany

Solvay Fluor Korea Co. Ltd
383, Daejung-Ri, Onsan-Eup
Ulju-kun, Ulsan, Korea
Telephone: +82 52 231 0020
Telefax: +82 52 231 0096
www.solvay-fluor.com

Solvay
Fluor Korea



Disclaimer: All statements, information, and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty or responsibility of any kind, express or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required. In any case, the user is not exempt from observing all legal, administrative and regulatory procedures relating to the product, personal hygiene, and protection of human welfare and the environment.

ANTAROX BL-225



Propoxylated ethoxylated linear alcohol
Concentration > 99 %

물리적 특성

Polarity: Nonionic
Density: 1.02 g/cm³
Boiling point: 200 °C
Viscosity (25°C): 142 mps
Flash point
(Cleveland open cup): 190 °C

규격

Appearance at 25°C:
clear to slightly
hazy liquid
Colour (Gardner): 3 max.
Water (K. Fischer): 0.5 %
Cloud point at 1 %: 25 –29 °C
Neutralisation number to
pH = 7 (mg KOH/g): max. 0.5

포장

Plastic bottle.
5 or 10 kg net weight.

분류

CAS No.: 68603-25-8
HS-No.: 34021300
Non-hazardous according
to current regulations.
EEC-Labeling
Symbol: Xi, N
R: 41, 51/53
S: 25, 36/37/39, 61

Safety recommendations and
additional information can be
found in the Material Safety Data
Sheet (MSDS).

용도

■ **Low foaming surfactant for
brazing flux suspensions**
(up to 50 °C)

Recommended concentration:
0.1 to 0.2%

MANAGEMENTSYSTEM



DQS – certified according

DIN EN ISO 9001:2000
Reg.-No. 360447 QM

ISO/TS 16949:2002
Reg.-No. 360447 TS2

NOCOLOK® 은 Solvay Fluor GmbH
에 등록된 상표입니다.

솔베이 케미칼 주식회사
울산시 울주군 온산읍 대정리 383
전화: 052-231-0020
팩스: 052-231-0096
www.solvay-fluor.com

Solvay
Fluor Korea



Disclaimer: All statements, information, and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty or responsibility of any kind, express or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required. In any case, the user is not exempt from observing all legal, administrative and regulatory procedures relating to the product, personal hygiene, and protection of human welfare and the environment.